

## DILUTE CLEANING COMPOSITION AND METHOD FOR USING SAME

### Abstract of the Disclosure

5 A cleaning method in a semiconductor fabrication process includes providing  
a dilute composition consisting essentially of phosphoric acid and acetic acid and  
exposing a surface, e.g., aluminum, to the dilute composition. For example, the dilute  
composition includes phosphoric acid at a concentration of about 5% or less by volume  
and acetic acid at a concentration of about 30% or less by volume. Further, the cleaning  
method may use a composition comprising phosphoric acid and acetic acid, wherein the  
10 composition includes phosphoric acid at a concentration of X%, wherein X is about 5%  
by volume or less, and acetic acid at a concentration of about (100-X%) by volume or  
less. The cleaning method may be used, for example, in fabricating interconnect  
structures, aluminum containing structures, and multilevel interconnect structures.  
Cleaning compositions for use in the cleaning methods are also provided.

15  
"EXPRESS MAIL" MAILING LABEL NUMBER

EL8883939954S

DATE OF DEPOSIT:

22 AUGUST 2001

I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING DEPOSITED WITH THE  
UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST OFFICE TO ADDRESSEE"

SERVICE UNDER 37 CFR 1.10 ON THE DATE INDICATED ABOVE AND IS ADDRESSED TO  
THE ASSISTANT COMMISSIONER FOR PATENTS. BOX PATENT APPLICATION  
WASHINGTON, D.C. 20231

PRINTED NAME

Gara L. Ludwig

SIGNATURE

Gara L. Ludwig